

DIELEKTRIČNI IZOLATORI

PN Nominalni pritisak

Materijal: Čelik


Radna temperatura: -15°C do 70°C

Napon izolacije na zraku: 3 kV

Otpor izolacije na zraku: 5 MΩ

Obojeno epoksidnom bojom

Dielektrični izolator ima funkciju da prekine prolaz statičkog elektriciteta i drugu protupožarnu, da na temperaturi većoj od 70 °C blokira protok plina širenjem specijalne mase.



Za zavarivanje



Navojni



	A	
PN 10	220	3/4"
	230	1"
	250	1 1/4"
	260	1 1/2"
	290	2"
	330	2 1/2"
	350	3"
PN 25	250	3/4"
	250	1"
	300	1 1/4"
	300	1 1/2"
	350	2"
	350	2 1/2"
	400	3"
	400	4"
	500	5"
	500	6"
	500	8"
	700	10"
	700	12"
PN 100	250	1/2"
	250	3/4"
	250	1"
	300	1 1/4"
	300	1 1/2"
	350	2"
	350	2 1/2"
	500	3"
	500	4"
	600	5"
	600	6"
	600	8"
	800	10"
	800	12"
PN 10	100	1/2"
	110	3/4"
	120	1"
	135	1 1/4"
	145	1 1/2"
	150	2"
M/F	170	2 1/2"
	200	3"
		4"